



# PANORAMIC 72.10

- Maximum Load Capacity: 7,200 kg (15,875 lb)
- Maximum Lift Height: 9.55 metres (31'4")
- Load at Maximum Height: 4,000 kg (8,820 lb)
- Load at Full Forward Reach: 2,000 kg (4,410 lb)
- Hydraulic Flow Rate of 108 l/min, 28.5 gal/min [Hydraulic Pump – Closed Centre Load Sensing]
- Towing capacity: 20,000 kg (44,100 lb)
- Frame levelling (+/- 9%)
- Tires: MITAS MPT-06 18-19.5
- Electro-proportional and mechanical joystick mounted on the body valve
- Engine: Tier 4i: Deutz/4-101 hp

## INTEGRATED OPTIONS

- Greasing interval (500 hours) with CSK bushings
- Powerful class 1 hydrostatic transmission
- Top speed of 40 km/h (25 mph)
- Integrated test port for no contamination of hydraulic circuit
- Anti-theft kit including lock of compartments with 12v switch
- Automatic quick attach with hydraulic Tack Lock™
- ¼" Ultra Sealed™ steel plate sealing the bottom of the chassis
- Automatic wheel resynchronization
- Dual control mode: novice/expert
- Electrohydraulic parking brake
- Extra-large cab (3.4' width)
- Low noise insulation
- Canadian Arctic package and homologation: fuel preheater, glow plug, block heater, oil, coolant, different hydraulic components and motor accessories
- Additional light kit
- On demand mechanical rear differential lock controlled from cab
- Towing hook
- Integrated boom sideshift with 4 anchor points and double levelling cylinders
- Air conditioning
- Grammer™ air suspension seat with arm support
- M-CDC Dynamic Load Control

## AVAILABLE OPTIONS

- Platform prearrangement for units of 10m and more
- Additional rear hydraulic line
- Paint in different colour (includes recalibration of paint shop)
- Backup camera

