



# MULTIFARMER 40.7 T CS-156

- Maximum Load Capacity: 4,000 kg (8,820 lb)
- Maximum Lift Height: 6.8 metres (22'4")
- Load at Maximum Height: 4,000 kg (8,820 lb)
- Load at Full Forward Reach: 1,900 kg (4,190 lb)
- Hydraulic Flow Rate of 152 l/min, 40 gal/min [Hydraulic Pump – Closed Centre Load Sensing & Flow Sharing]
- Frame levelling (+/- 10%)
- Tires: Michelin XMCL 500/70R24
- Engine: Tier 4i: Deutz 4-156 hp

## INTEGRATED OPTIONS

- Greasing interval (500 hours) with CSK bushings (except wheel reducers)
- Continuously variable transmission (MCVTronic™)
- Top speed of 40 km/h (25 mph)
- Integrated test port for no contamination of hydraulic circuit
- Anti-theft kit including lock of compartment with 12v switch
- Automatic quick attach with hydraulic Tack Lock™
- 1/4" Ultra Sealed steel plate sealing the bottom of the chassis
- Automatic wheel resynchronization
- Dual control mode: novice/expert
- Electrohydraulic parking brake
- New generation extra-large cab (3'4" width)
- Cab suspension
- Low noise insulation
- Canadian Arctic package and homologation: fuel preheater, glow plug, block heater, oil, coolant, different hydraulic components and motor accessories
- Additional light kit
- On demand mechanical rear and front differential lock controlled from cab
- Rear mechanical PTO (135 hp) including multi-position towing hook
- Air conditioning
- Grammer™ air suspension seat with arm support
- Continuous oil flow
- Advance cushion system on the boom (B.S.S.) (N/A with platform prearrangement)
- Eco Mode button
- Speed control
- M-CDC Dynamic Load Control
- Electric socket for trailer light



## SPECIFIC INTEGRATED OPTIONS

- 3 points linkage with 7,000 kg capacity including external operation
- 4 x double acting hydraulic rear services

## AVAILABLE OPTIONS

- Prearrangement for platform
- Painted in different colour (includes recalibration of paint shop)
- Front window protection
- Back up camera