



# PANORAMIC 25.6/25.6L

- Maximum Load Capacity: 2,500 kg (5,510 lb)
- Load at Maximum Height: 1,750 kg (3,860 lb)
- Hydraulic Flow Rate of 84 l/min, 22 gal/min
- Engine: Tier 3A: Kubota/4-75 hp
- Maximum Lift Height: 5.9 metres (19'4")
- Load at Full Forward Reach: 1,000 kg (2,200 lb)
- Tires: MITAS TR3 12/75-18

## INTEGRATED OPTIONS

- Electro-mechanical joystick mounted on the body valve, including inverter (forward/reverse)
- Lower greasing interval (500 hours) with CSK bushings\* (except wheel reducers)
- Class 1 hydrostatic transmission
- Top speed of 40 km/h (25 mph)
- Integrated test port for no contamination of hydraulic circuit
- Anti-theft kit including lock of compartments with 12v switch
- Hydraulic Tack Lock™ quick attach controlled from the cab
- Ultra Sealed™ by 1/4" steel plate under chassis
- Automatic wheel resynchronization
- Dual control mode: novice/expert
- Electrohydraulic parking brake
- Extra-large cab (3.4' width)
- Low noise insulation
- Canadian Arctic package and homologation: fuel preheater, glow plug, block heater, oil, coolant, different hydraulic components and motor accessories
- Additional light kit
- Mechanical rear differential lock controlled from cab "on demand"
- Towing hook
- Air conditioning
- Grammer™ air suspension seat with arm support (N/A on low profile cab)

## AVAILABLE OPTIONS

- Platform prearrangement
- Continuous oil flow
- Rear service with independent control
- Paint in different colour (includes recalibration of paint shop)
- Low profile cab (5.9 inches lower)



SKID STEER, MINI-LOADER AND OTHER COMPACT TELEHANDLERS WORST ENEMY

