



# PANORAMIC 40.17/ECO

- Maximum Load Capacity: 4,000 kg (8,820 lb)
- Maximum Lift Height: 16.7 metres (54'10")
- Load at Maximum Height: 2,500 kg (5,510 lb)
- Load at Full Forward Reach: 500 kg (1,100 lb)
- Hydraulic Flow Rate of 115 l/min, 30.4/min [Hydraulic Pump – Closed Centre Load Sensing]
- Frame levelling (+/- 10%)
- Electro-proportional and mechanical joystick mounted on the body valve
- Tires: MITAS MPT-01 405/70-24
- Engines: Tier 4i: Deutz/4-101 hp - ECO: Tier 3A: Kubota/4-75 hp

## INTEGRATED OPTIONS

- Greasing interval (500 hours) with CSK bushings
- Powerful class 1 hydrostatic transmission
- Top speed of 40 km/h (25 mph)
- Integrated test port for no contamination of hydraulic circuit
- Anti-theft kit including lock of compartments with 12v switch
- Automatic quick attach with hydraulic Tack Lock™  
8 mm Ultra Sealed™ steel plate sealing the bottom of the chassis
- Automatic wheel resynchronization
- Dual control mode: novice/expert
- Electrohydraulic parking brake
- Extra-large cab (3.4' width)
- Low noise insulation
- Canadian Arctic package and homologation: fuel preheater, glow plug, block heater, oil, coolant, different hydraulic components and motor accessories
- Additional light kit
- On demand mechanical rear differential lock controlled from cab
- Towing hook
- Integrated boom sideshift with 4 anchor points and double levelling cylinders
- Narrow and independent outriggers, rapid deployment on tested ground (on axles, not chassis)
- M-CDC Dynamic Load Control

## AVAILABLE OPTIONS

- Electronic active suspension on the front axle (A.E.S.)
- Platform prearrangement (300 kg or 800/1,000 kg)
- Remote control and platform standard prearrangement (Includes control box with remote control function)
- Space system and platform standard prearrangement (Includes control box with remote control and space function)
- Paint in different colour (includes recalibration of paint shop)
- Air conditioning
- Grammer™ air suspension seat with arm support
- Backup camera

