

**NEW MODEL**

# TURBOFARMER 42.7 CS-156-PTO

- Maximum Load Capacity: 4,200 kg (9,260 lb)
- Maximum Lift Height: 7.1 metres (23.3')
- Load at Maximum Height: 3,500 kg (7,720 lb)
- Load at Full Forward Reach: 1,600 kg (3,530 lb)
- Hydraulic Flow Rate of 178 l/min, 47 gal/min [Hydraulic Pump – Closed Centre Load Sensing & Flow Sharing]
- Towing capacity: 20,000 kg (44,100 lb)
- Tires: MICHELIN XMCL 460/70-24
- Engine: Deutz Tier 4i 156 hp

## INTEGRATED OPTIONS

- Electronic joystick, including inverter (forward/reverse)
- Greasing interval (500 hours) with CSK bushings
- Powerful class 1 hydrostatic transmission with EPD (Eco Power Drive™) (18% in fuel savings vs standard hydrostatic)
- Top speed of 40 km/h (25 mph)
- Anti-theft kit including lock of compartments with 12v switch
- Automatic quick attach with hydraulic Tack Lock™
- ¼" Ultra Sealed™ steel plate sealing the bottom of the chassis
- Automatic wheel resynchronization
- Dual control mode: novice/expert
- Electrohydraulic parking brake
- Extra-large cab of new generation (3.4' width)
- Low noise insulation
- Canadian Arctic package and homologation: fuel preheater, glow plug, block heater, oil, coolant, different hydraulic components and motor accessories
- Additional lights kit (S770)
- On demand mechanical rear differential lock controlled from cab
- Multi-positions towing hook
- Air conditioning
- Grammer™ air suspension seat with arm support
- Continuous oil flow
- Hydraulic reversible fan
- Advance cushion system on boom (B.S.S.) (N/A with platform prearrangement)
- CS cab suspension
- Rear mechanical PTO (135 hp)
- 2 rear hydraulic lines with selector
- Cruise control
- M-CDC Dynamic Load Control

## AVAILABLE OPTIONS

- Platform prearrangement for units of 10m or less
- 3rd rear hydraulic line available under certain restrictions
- Continuously variable transmission (MCVTronic™)
- TT (sideshift and frame leveling)
- Backup camera

